



1700 Series

Cold-Water Pressure Washers

Rugged and powerful, this cold-water pressure washer is great for in-plant applications such as food service, agriculture and industrial. The 1700 Series also works great as a central cleaning system.

Choose From 20 Models



■ **Quick disconnect nozzles** are color-coded for quick and easy changing between 0°, 15°, 25°, 40° spray nozzles.



■ **Hawk® triplex, belt-drive pump** carries seven-year crankcase and lifetime manifold warranties.

■ **Stainless steel, variable-pressure, dual-lance wand** for remote detergent on/off.

Model 1720 shown in optional stainless steel.

■ **Tri-lingual labels** provide operating instructions in English, Spanish and French.

■ **Down-stream detergent injection** allows remote detergent application.



■ **50-ft. high-pressure, non-marking hose** for easy maneuverability around a large working area.

■ **Standard hour meter** accurately tracks in-use service time.

■ **Belt-drive motor** ensures a smooth- and quiet-running machine.

■ **Industrial motor and overloads** provide solid machine performance.

Model 1720 shown with optional wheel kit.



The 1700 Series boasts a simple, yet extremely efficient, design. Cast-iron pulleys offer longer belt life. Belts are easily adjusted by turning two bolts. Notched V-belts provide cooler operation.





Optional cart and caster wheel kits are available for machine mobility.

Hotsy's 1700 Series provides heavy-duty cleaning power for in-plant or wash bay applications.

From food service, agriculture, industrial and more, the popular 1700 Series is designed to deliver big cleaning performance in a compact, versatile package. The 1700 Series is available in a variety of specifications to meet your cleaning needs including 208V/1PH, 208V/3PH, 230V/1PH, 230V/3PH and 460V/3PH.

Discover Hotsy's no-cost benefits

Choose the 1700 Series for its high performance and reliability. Then enjoy the benefits of doing business

with the leader in industrial cleaning equipment. You'll find more than 120 models of pressure washers to choose from, free on-site demos, factory-trained service people, pre-delivery dealer prep, on-site machine check-out, operator training, local parts and accessory inventory and an unbeatable warranty program.

Accessories to match your application

Hotsy's custom accessories tailor the 1700 Series pressure washer to fit your specific requirements making your cleaning jobs faster, easier and more efficient. Choose from portable wheel kits, floor stands, wall mount kits, time delay shut down, stainless steel base and cabinet, extra hose lengths, hose reels, wand extensions, quick couplers, foam applicator, wet sandblaster, rotating brush and more.



Clean better with Hotsy detergents

Hotsy's broad selection of biodegradable detergents are formulated specifically for high-temperature, high-pressure cleaning. This means you get the best results from your Hotsy pressure washer while continuously protecting the machine. Exclusive advanced-formula Hotsy Continuous Clean(HCC) additives continuously clean the lime and mineral buildup that can occur in your washer's coil and fittings.



This cleaning action reduces replacement costs and improves machine performance. Most Hotsy detergents are USDA and Canadian Agriculture approved. And they're concentrated, so a little goes a long way.

Call today for a demo!

Find out for yourself why the Hotsy 1700 Series is right for your cleaning jobs. Call your Hotsy distributor today for all the details and a FREE on-site demo.



1700 Series Specifications

1720:	3.9 GPM @ 2000 PSI;	6 HP; 230V; 1PH electric motor; ship wt.: 291 lbs.
1722:	3.9 GPM @ 2000 PSI;	6 HP; 208V; 1PH electric motor; ship wt.: 291 lbs.
1723:	3.9 GPM @ 2000 PSI;	6 HP; 208V; 3PH electric motor; ship wt.: 291 lbs.
1724:	3.9 GPM @ 2000 PSI;	6 HP; 230V; 3PH electric motor; ship wt.: 291 lbs.
1725:	3.9 GPM @ 2000 PSI;	6 HP; 460V; 3PH electric motor; ship wt.: 291 lbs.
1730:	3.5 GPM @ 3000 PSI;	7.5 HP; 230V; 1PH electric motor; ship wt.: 303 lbs.
1732:	3.5 GPM @ 3000 PSI;	7.5 HP; 208V; 1PH electric motor; ship wt.: 303 lbs.
1733:	3.5 GPM @ 3000 PSI;	7.5 HP; 208V; 3PH electric motor; ship wt.: 303 lbs.
1734:	3.5 GPM @ 3000 PSI;	7.5 HP; 230V; 3PH electric motor; ship wt.: 303 lbs.
1735:	3.5 GPM @ 3000 PSI;	7.5 HP; 460V; 3PH electric motor; ship wt.: 303 lbs.
1740:	4.8 GPM @ 3000 PSI;	10 HP; 230V; 1PH electric motor; ship wt.: 319 lbs.
1742:	4.8 GPM @ 3000 PSI;	10 HP; 208V; 1PH electric motor; ship wt.: 319 lbs.
1743:	4.8 GPM @ 3000 PSI;	10 HP; 208V; 3PH electric motor; ship wt.: 319 lbs.
1744:	4.8 GPM @ 3000 PSI;	10 HP; 230V; 3PH electric motor; ship wt.: 319 lbs.
1745:	4.8 GPM @ 3000 PSI;	10 HP; 460V; 3PH electric motor; ship wt.: 319 lbs.
1750:	5.9 GPM @ 2500 PSI;	10 HP; 230V; 1PH electric motor; ship wt.: 319 lbs.
1752:	5.9 GPM @ 2500 PSI;	10 HP; 208V; 1PH electric motor; ship wt.: 319 lbs.
1753:	5.9 GPM @ 2500 PSI;	10 HP; 208V; 3PH electric motor; ship wt.: 319 lbs.
1754:	5.9 GPM @ 2500 PSI;	10 HP; 230V; 3PH electric motor; ship wt.: 319 lbs.
1755:	5.9 GPM @ 2500 PSI;	10 HP; 460V; 3PH electric motor; ship wt.: 319 lbs.

Water Pump Volume:	3.5 GPM (13.2 lpm)/210 GPH (792 lph); 3.9 GPM (14.8 lpm)/234 GPH (888 lph); 4.8 GPM (18.2 lpm)/288 GPH (1092 lph); 5.9 GPM (22.4 lpm)/354 GPH (1345 lph)
Water Pump Pressure:	2000 PSI (138 bars); 2500 PSI (172 bars); 3000 PSI (207 bars).
Water Pump:	Hawk® triplex, belt-drive, positive-displacement pump; ceramic plungers, brass manifold, oil-bath crankcase.
Pump Drive:	6, 7.5 or 10 HP, 208V, 230V or 460V, 60 Hz, 1PH or 3PH electric motor; open drip proof with thermal overload protection.
Controls:	Magnetic motor starter and industrial rocker on/off switch for pump motor.
Wand Assembly:	Stainless steel with variable pressure.
Nozzle:	Quick disconnect-type hardened stainless steel (0°, 15°, 25°, 40°); Brass (Detergent)
Hose:	3/8" ID, 50 ft. wire braid with swivel fittings at both ends; 3000 PSI working pressure; burst pressure is at least 4 times working pressure; oil and chemical resistant.
Portability:	Optional
Optional Accessories:	Stainless steel construction, time delay shut down, wheel kit with detergent rack, floor stand (short or tall), caster kit for floor stand, wall mount kit, extra hose lengths, hose reel kits (for floor stand or wall mount options), wand extensions, quick couplers, wet sandblaster, rotating brush and foam applicator.
Construction:	Durable, heavy-gauge sheet metal.
Finish:	High-gloss, powder coat or stainless steel (optional).
Dimensions:	L-30.50" (77.47 cm); W-20.88" (53.03 cm); H-16.25" (41.28 cm)



21 Inverness Way East, Englewood, Colorado 80112-5796 Tel: (303) 792-5200
1-800-525-1976 Fax: (303) 792-0547 e-mail: info@hotsy.com or visit our
website: www.hotsy.com

P/N 97-0485 Printed in USA Effective 7/01 Specifications and product
descriptions subject to change without notice. © 2001 Hotsy

America's #1 Manufacturer of Cleaning Systems

