



UNIVERSAL CLEANING SOLUTIONS

The Model 560SS is an ideal cleaning system for commercial, agricultural, manufacturing and municipal applications.

# MODEL 560SS

## Hot-Water Pressure Washer

### 2.3 GPM @ 1500 PSI

■ **Hose reel** (optional) makes hose mobility and storage easy and convenient. Also keeps work areas neat and safe while protecting hoses from damage.



■ **Simple, easy-to-use control panel** includes adjustable temperature control plus heavy-duty heater and pump motor switches.

■ **Stainless-steel coil skin** provides extra durability to withstand the elements.

■ **Built-in wand holder** provides convenient storage.

■ **Upright, oil-fired burner** delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil.

■ **2.3 HP, 115V, 1PH electric motor** is drip proof and comes with thermal overload protection and manual reset.

■ **Convenient hose-reel bracket** accepts swivel or stationary reels for ease in hose maneuverability and storage.

■ **Pressure-relief valve** protects the machine and user.

■ **50-ft. length of high-pressure hose** for easy maneuverability around a large working area.

■ **Adjustable upstream detergent injection** ensures high-pressure sudsing for better cleaning.

■ **37-ft. power cord** with safety **Ground Fault Circuit Interrupter (GFCI breaker)**.



■ **Float tank** helps maintain constant pressure and helps prevent sediment from entering the machine's components.

■ **Rust-proof, non-contaminating polyethylene fuel tank** includes fuel gauge in cap.



■ **Hotsy triplex, direct-drive, positive-displacement pump** carries seven-year crankcase and lifetime manifold warranties.

■ **Adjustable, spray-angle nozzle** with 0° to 80° spray patterns adjusts easily under high pressure.

■ **Semi-pneumatic wheels** eliminate the risk of flats.



## Hotsy's Model 560SS is powerful enough to tackle your toughest cleaning tasks

Powerful, yet versatile, the Model 560SS supplies a steady stream of 2.3 GPM hot water at 1500 PSI. This combination of cleaning power along with convenient portability – all at an economical price – makes the Model 560SS an excellent choice for blasting away caked-on mud, dirt, grease and grime in commercial, agricultural, manufacturing and municipal applications.

### Discover Hotsy's no-cost benefits

Choose the Model 560SS for its high performance and reliability. Then enjoy the benefits of doing business with the leader in industrial cleaning equipment. You'll find more than 120 models of pressure washers to choose from, free on-site demos, factory-trained service people, pre-delivery dealer prep, on-site machine checkout, operator training, local parts and accessory inventory, and a quality warranty program.

### Accessories to match your application

Hotsy's custom accessories tailor the Model 560SS pressure washer to fit your specific requirements, making your cleaning jobs faster, easier and more efficient. Choose from extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, foam applicator, wet sandblaster, rotating brush and more.



### Clean better with Hotsy detergents

Hotsy's broad selection of biodegradable detergents are formulated specifically for high-temperature, high-pressure cleaning. This means you get the best results from your Hotsy pressure washer, as well as protect it. Exclusive advanced-formula HCC additives continuously clean the lime and mineral buildup that can occur in your washer's coil and fittings. This cleaning action reduces replacement costs and improves machine performance. Most Hotsy detergents are USDA and Canadian Agriculture approved. And they're concentrated, so a little goes a long way.

### Call today for a demo!

Find out for yourself why the Hotsy Model 560SS is right for your tough cleaning tasks. Call your Hotsy Distributor today for all the details and a FREE on-site demo.



21 Inverness Way East, Englewood, Colorado 80112-5796 Made with PRIDE  
Tel: (303) 792-5200 **1-800-525-1976** Fax: (303) 792-0547 in the USA  
e-mail: info@hotsy.com or visit our website: www.hotsy.com

P/N 768921B Printed in USA Effective 8/02 Supercedes 768921A (7/01)  
Specifications and product descriptions subject to change without notice.  
© 2002 Hotsy

## Model 560SS Specifications

**2.3 GPM @ 1500 PSI; 2.3 HP, 115V, 1-phase electric motor; 20 Amp; oil-fired water heater; shipping weight: 372 lbs.**

**Water Pump Volume:** 2.3 GPM (8.70 lpm); 138 GPH (522.22 lph).

**Water Pump Pressure:** 1500 PSI (103.45 bars).

**Water Pump:** Hotsy triplex, direct-drive, positive-displacement pump; ceramic plungers, brass manifold, oil-bath crankcase.

**Pump Drive:** 2.3 HP, 115V, 60 Hz, 1PH electric motor; 56 frame, open, drip-proof with thermal overload protection and manual reset.

**Water Heater:** Oil fired, 197,000 BTU/hr., UL-listed burner; pressure-atomizing type with automatic electric ignition. Your choice of #1 or #2 diesel, kerosene or #1 home heating oil as fuel. Fuel filter standard. Color-coded fuel lines indicate direction of flow. 8-gallon, removable, rust-proof, non-contaminating, polyethylene fuel tank with fuel gauge in cap.

**Heating Coil:** Schedule 80, ASTM A53 close coiling pipe; vertically fired, hydrostatic pressure tested. Heating coil is sheathed in a full-length sheet-metal wrap. Equipped with an independently welded heat-retention baffle plate.

**Stack Size:** 8" diameter.

**Controls:** Adjustable temperature control; self-cleaning, safety pressure-relief valve; heavy-duty rocker type ON/OFF pump motor and water-heater switches; upstream detergent injector.

**Wand Assembly:** Trigger-gun control with cool grip, quick-coupled to heavy-duty, chrome-plated wand with insulated grip.

**Nozzle:** Adjustable, spray-angle nozzle with 0° to 80° degree spray patterns. Adjusts easily even under high pressure.

**Hose:** 3/8" ID, 50 ft. wire braid with swivel fittings at both ends. 3000 PSI working pressure; burst pressure is at least 4 times working pressure; oil and chemical resistant.

**Portability:** Standard; heavy-duty, semi-pneumatic, Ace-Tuf®, ball-bearing wheels.

**Optional Accessories:** Extra hose lengths, hose reels (hose reel bracket standard), wand extensions, quick couplers, downstream detergent injector, wet sandblaster, rotating brush and foam applicator.

**Construction:** Durable, heavy-gauge sheet-metal chassis.

**Finish:** High-gloss, powder coat.

**Dimensions:** L-42" (106.68 cm), W-30" (76.20 cm), H-49" (124.46 cm).

