



700 Series

Hot-Water Pressure Washers

The 700 Series models melt away stubborn dirt, caked-on mud, thick grease, road film and grime.

3 GPM @ 1500 PSI

■ **3 HP, 208-230V, 1PH electric motor** is drip proof and comes with thermal overload protection and manual reset.

■ **Simple, easy-to-use control panel** includes high-limit temperature control with precision safety controls.

■ **Stainless-steel coil skin** provides extra durability to withstand the elements.

■ **Adjustable upstream detergent injection** ensures high-pressure sudsing for better cleaning.

■ **Convenient hose reel bracket** accepts swivel or stationary reels.



■ **Hotsy triplex, positive-displacement pump** carries seven-year crankcase and lifetime manifold warranties.

■ **Adjustable spray-angle nozzle** with 0° to 80° spray patterns adjusts easily under high pressure.

■ **Rust-proof, removable, non-contaminating polyethylene fuel tank** includes fuel gauge in cap.

■ **Semi-pneumatic wheels** eliminate the risk of flats.



■ **50-ft. length of high-pressure hose** for ease in cleaning around a large area.

■ **Upright, oil-fired burner** delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil.

■ **Built-in wand holder** provides convenient storage.

Shown is Model 770SS:
3 GPM @ 1500 PSI



Hotsy Model 771, LP-gas-fired pressure washer. Shown with optional wheel kit and tank rack (PIN 280771). Tank not supplied.

The Model 770SS oil-fired pressure washer is shown on the reverse side.

Flexible workhorses for thousands of cleaning tasks

The popular 700 Series includes oil-fired, natural-gas and LP-gas-fired models. They are powered by 3 HP electric motors to provide 3 GPM of hot water at 1500 PSI. The combination of power, portability and affordability makes the 700 Series an excellent choice for blasting away dirt, grease and grime in countless industrial, commercial and municipal applications.

Dependable Hotsy® triplex Pump

Our Hotsy triplex, direct-drive, positive-displacement pump outputs a continuous 1500 PSI to handle a wide range of cleaning jobs. The Hotsy pump is your assurance of pressure-packed cleaning combined with long, trouble-free life.

Accessories to match your application

With their easy adaptability, the 700 Series models are prime candidates for Hotsy's full line of accessories. You can custom tailor the washer to your specific requirements, making your cleaning jobs faster, easier and more efficient. Choose from portable wheel kits, extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, foam applicator, wet sandblaster, rotating brush and more.

Clean better with Hotsy detergents

Hotsy's broad selection of biodegradable detergents are formulated specifically for high-temperature, high-pressure cleaning. This means you get the best results from your Hotsy pressure washer while continuously protecting it. Exclusive advanced-formula HCC additives continuously clean the lime and mineral buildup that can occur in your washer's coil and fittings. This cleaning action reduces replacement costs and improves machine performance. Most Hotsy detergents are USDA and Canadian Agriculture approved. And they're concentrated, so a little goes a long way.

Call today for a FREE Demo!

Find out for yourself why the Hotsy 700 Series is the ideal solution for your most difficult cleaning tasks. Call your Hotsy Distributor today for all the details and a FREE on-site demonstration.



21 Inverness Way East, Englewood, Colorado 80112-5796
Tel: (303) 792-5200 **1-800-525-1976** Fax: (303) 792-0547
e-mail: info@hotsy.com or visit our website: www.hotsy.com

Built with PRIDE in the USA

P/N 97-0473E Printed in USA Effective 5/03 Supercedes 885307D (11/02)
Specifications and product descriptions subject to change without notice. © 2003 Hotsy

America's #1 Manufacturer of Cleaning Systems



Models 770SS, 771 & 772 Specifications

770SS:	3 GPM @ 1500 PSI, 3 HP, 208-230V electric motor; oil-fired water heater; shipping weight 362 lbs.
771:	3 GPM @ 1500 PSI; 3 HP, 208-230V, electric motor; LP-gas-fired water heater; shipping weight 390 lbs.
772:	3 GPM @ 1500 PSI; 3 HP, 208-230V, electric motor; Natural-gas-fired water heater; shipping weight 390 lbs.

SPECIFICATIONS

Water Pump Volume:	3 GPM (11.36 lpm); 180 GPH (681.3 lph)
Water Pump Pressure:	1500 PSI (103.5 bar)
Water Pump:	Hotsy triplex, direct-drive, positive displacement pump; ceramic plungers; brass manifold; oil-bath crankcase.
Electric Pump Motor:	3 HP electric motor, 208-230V, 60Hz, 1 PH; 56 frame, "C" face; open drip-proof.
Oil-Fired Water Heater:	770SS: 290,000 BTU/hr. UL-listed burner, pressure-atomizing type with automatic electronic ignition. Choice of #1 or #2 diesel fuel, kerosene or #1 home heating oil as fuel. Fuel filter standard. Color-coded fuel lines indicate direction of flow. 8-gallon, removable, rust-proof, non-contaminating, polyethylene fuel tank. Fuel gauge in cap.
Gas-Fired Water Heater:	771/772: 350,000 BTU/hr. ring-type burner with aspirating spuds; natural draft with hot-surface electronic igniter. Vapor-type LP-gas tank required, but not included.
Heating Coil:	Schedule 80, ASTM A53 close coiling pipe; hydrostatic pressure tested; vertically fired. Heating coil is sheathed in a full-length sheet-metal wrap. Equipped with an independently welded heat-retention baffle plate.
Stack Size:	8" oil fired; 10" gas fired (gas-fired units require draft diverter).
Controls:	Adjustable temperature control, safety pressure relief valve, high-pressure detergent injector. Pump switch, heavy-duty toggle type; water heater, heavy-duty rocker type (thermal overload protected).
Wand Assembly:	Trigger-gun control with cool grip, quick coupled to a heavy-duty chrome-plated wand with insulated grips.
Nozzle:	Easily adjustable variable fan spray nozzle with 0° through 80° spray patterns.
Hose:	3/8" ID, 50 ft., wire braid, 3000 PSI working pressure; burst pressure is at least 4 times working pressure; oil and chemical resistant. Swivel fittings both ends.
Portability:	Standard on Model 770SS. Optional on Model 771. Heavy-duty, semi-pneumatic wheels. Not available on Model 772.
Optional Accessories:	Extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, wet sand blaster, rotating brush, foam applicator and draft diverter.
Construction:	Durable, heavy-gauge sheet-metal chassis.
Finish:	High-gloss, powder coat.
Dimensions:	770SS: L-44" (111.8 cm); W-36" (91.44 cm); H-41" (104.14 cm) 771/772: L-31.5" (80.01 cm); W-20" (50.8 cm); H-36.5" (92.71 cm)

All machines are ETL Certified to UL 1776 Standards and to CSA

